HELLONEXT

POWERED BY Petrotec

EV-CHARGERS

PRICE-LIST

2022

> Table

AC/DC	Type	Version		Pg
AC	Wall	H1 7L	BASIC	3
			WiFi (RFID)	3
			4G (RFID)	3
		H1 22W	BASIC	3
			MID	3
	Free Standing	H1 22		4
DC	Movable	H2 30M		5
	Wall	H2 30 S		5
		H2 30 D		5
	Free Standing	H2 60		6
		H2 90		6
		H2 120		6
		H2 150		6
		H2 180		6
	Cabinet	H2 360	Power Cabinet	7
			Sat Air Cooled	7
			Sat Liquid Cooled	7

» Prices Exworks @Guimarães

» Customizable Livery

» Delivery in 8-10 Weeks

AC EV-CHARGERS

> H1 7L

» Input: 200Vac~240Vac
» Wall mounted
» Optional wired / wireless connection
» Optional RFID card reader
» IP55 rated for indoor/outdoor applications
» Firmware updates through remote connection
» Charging Interface: IEC 62196 (Type 2)
» Single output from 3,7 kVA to 7,4 kVA

Version
BASIC
WiFi (RFID)
4G (RFID)

> H1 22W

» Input: 380~415Vac
» Modern, ergonomic and customizable design
» wired / wireless connection
» RFID card reader
» Optional 5" LCD
» IP56 rated for indoor/outdoor applications
» Supports Over the Air Technology (OTA)
» Charging Interface: IEC 62196 (Type 2)
» Single output from 3,7 kVA to 22 kVA
» Optional Socket / Cable&Gun version

Version
BASIC
MID

AC EV-CHARGERS

> H1 22

» Input: 400 VAC
» Pole mounted with display
» Firmware updates through remote connection
» IP54 rated for indoor/outdoor applications
» RFID card reader
» Optional wireless (4G) connection
» Charging interface: IEC 62196-2 (Type 2)
» Dual individual output from 11 kVA to 22 kVA
» Optional Socket / Cable&Gun version

Version
H1 22

DC EV-CHARGERS

> H2 30

> H2 30M

» Efficiency > 94% ; PF> 0.99 (APFC)
» Supports Ethernet, 4G or Wi-Fi
» Support smart charging and load balancing
» Network or standalone operation
» User authentication
» 7" LCD with a user-friendly interface
» IK10, IP55
» Output Power of 30 Kw
» Single or Dual Gun

Version
H2 30 S
H2 30 D
H2 30M

DC EV-CHARGERS

> H2 60

> H2 90 – 180

» Efficiency > 94% : PF > 0,99 (APFC)
» Support simultaneous smart charging and load balancing
» Optional cable management accessories
» Network or standalone operation
» 7" LCD screen with user friendly interface
» User authentication
» Multi-standard: CCS and CHAdeMO
» IK10, IP55
» Prepared for AC MID / DC Meter
» Modular Output Power from 60 Kw to 180Kw

Version
H2 60
H2 90
H2 120
H2 150
H2 180

Option
AC Plug*
AC Meter (MID)
Cable Management

* Only H2 60

DC EV-CHARGERS

> H2 360

» Efficiency > 94% : PF > 0,99 (APFC)
» Support simultaneous smart charging and load balancing
» Power cabinet supports Pantograph Charging
» Network or standalone operation
» 7" LCD screen with user friendly interface
» User authentication
» Multi-standard: CCS and CHAdeMO
» IK10, IP55
» Supports 4 simultaneous vehicles charging up to 360 kW

Version
Power Cabinet
Air Cooled Satellite
Liquid Cooled Satellite

PRICELIST

AC/DC	Type	Version	
AC	Wall	H1 7L	BASIC
			WiFi (RFID)
			4G (RFID)
		H1 22W	BASIC
			MID
	Free Standing	H1 22	
DC	Movable	H2 30M	
	Wall	H2 30 S	
		H2 30 D	
	Free Standing	H2 60	
		H2 90	
		H2 120	
		H2 150	
		H2 180	
	Cabinet	H2 360	Power Cabinet
			Sat Air Cooled
			Sat Liquid Cooled
Customized Livery			

» Prices Exworks @Guimarães

» Delivery in 8-10 Weeks